



Survivor® LED Flashlight

Case Material: Lamp housing, battery housing and alkaline battery base are made from high impact super tough nylon. All openings are O ring-sealed. Spring loaded clip with built in attachment ring attaches to belts and harnesses. One way valve for case venting. Available in international safety orange or high visibility yellow.

Dimensions: Height: 6.75 in. (17.15 cm) Height in charger: 8.50 in. (21.6 cm)
 Width: 2.85 in. (7.24 cm) Diameter: 2.87 in. (7.29 cm)

Grip area:

Height: 3.6 in. (9.14 cm) Thickness: 1.35 in. (3.43cm) Width: 2.20 in. (5.59 cm)

Weight: Ni-Cd: 17.9 oz (508 grams)*, Alkaline: 13.1 oz (371 grams)*

Lens: Unbreakable Lexan® Lens with silicone anti-scratch coating is assembled in a heavy duty bezel. O-ring sealed.

Light Source: 50,000 hr life Luxeon® LED

Light Output: Up to 65 Lumens typical

On/Off: Raised push-button switch for easy use with gloves. 3-position switch: high, low, locator strobe light

Run Time: Operational between charges for up to 6 hrs on low beam, 3 hrs high beam; with rechargeable or alkaline batteries

Battery: Industrial rechargeable nickel-cadmium 4.8 volt, 1.8 amp hour, 4 cell sub-C; can be recharged up to 1,000 times; or 4 "AA" alkaline batteries

Charging: AC and DC one-hour fast chargers with full charge indicators designed specifically for AC or DC power sources. The universal Steady Charger, which requires up to 10 hours for a complete charge, can be used with 110V, 120V, 230V, 240V, or 12V DC by exchanging its charge cord.

- Features:**
- Rechargeable model fits all existing Survivor charging units and accepts existing batteries
 - Microprocessor controls 2 levels of brightness - high/low beam and flash
 - Water resistant

Approvals:** DIVISION 1: UL Listing applied for with battery 90130 and 4 AA sized Alkaline.
 DIVISION 2: UL Listing applied for with battery 90338 and 4 AA sized Alkaline.
 Rack meets requirements of NFPA 1901-12-1.7 mounted in any position.
 Most models meet applicable European Community Directives.

Warranty: "No Excuses" limited lifetime warranty.

*With battery (included in purchase)

** See product for specific ratings.



Survivor® LED Model Part Numbers		
Steady Charge Model*		
Survivor LED w/ AC/DC	Yellow	90513
Survivor LED w/ AC/DC	Orange	90503
Fast Charge Model*		
Survivor LED w/ AC	Yellow	90512
Survivor LED w/ AC	Orange	90502
Survivor LED w/DC	Yellow	90519
Survivor LED w/DC	Orange	90509
Light Only (Rechargeable)		
Survivor LED	Yellow	90510
Survivor LED	Orange	90500
Alkaline Model		
Survivor LED	Yellow	90541
Survivor LED	Orange	90540

Survivor® LED Accessories Part Numbers	
Steady Charge (SC) Plug-In Charger Holder	#90010
Steady Charge (SC) PiggyBack Charger	#90110
AC Fast Charger (Includes Holder)	#90011
DC #1 Fast Charger (Includes Holder)	#90012
DC #2 Fast Charger (Includes Holder)	#90013
Bank Charger, (SC) 120 volt AC	#90400
Bank Charger, 12V DC	#90401
120 volt AC Charge Cord	#22311
12 volt DC1 Charge Cord	#22051
12 volt DC2 Direct Wire Charge Cord	#22050
Battery Pack Assembly – Division 1	#90337
NiCd Battery Pack Assy	#90338
Alkaline Battery Pack	#90542
Facecap Assembly (Division 1 & 2)*	#90330
Bezel/Lens Assembly*	#90054

*Image not available



Survivor – (W/out Charger)	Yellow	#91225
Survivor – (W/out Charger)	Orange	#91025



120V AC charge cord	#22311
12V DC cigarette lighter charge cord	#22051
12V DC direct wire charge cord	#22050



Battery Pack Assembly	#90337
Battery Pack Assembly – AA Alkaline	#90542



Bank Charger, (SC) 120 volt AC	#90400
Bank Charger, DC	#90401



Steady Charge (SC) Plug-In Charger Holder	#90010
Steady Charge (SC) PiggyBack Charger	#90110



AC Fast Charger	#90011
DC #1 Fast Charger (DC Configuration not shown)	#90012
DC #2 Fast Charger (DC Configuration not shown)	#90013